



Form A - EN 175301-803 (DIN43650) / ISO 4400

Product description		EN175301-803	EN175301-803
Standard		EN175301-803	EN175301-803
Construction type		A	A
Description		P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and protective circuit (diode)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and protective circuit (diode)
Housing colour		transparent	transparent
Number of contacts		2+PE	2+PE
Order no.		KA132D54T9	KA132D54T1
Other options on request	led colour red led colour green	order no. KA132D57T9 order no. KA132D5AT9	order no. KA132D57T1 order no. KA132D5AT1
Cable gland		PG9 (M16x1,5 on request)	PG11
Max. conductor size		1,5mm ² without splice/terminal	1,5mm ² without splice/terminal
Drawing			
Technical data			
Pin dimension		6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
Voltage		24 V DC	24 V DC
Rated current max.		4 A	4 A
Suppressor		Diode 1A 1000V	Diode 1A 1000V
LED colour		yellow	yellow
Contact resistance		15mΩ max.	15mΩ max.
Overvoltage category		III	III
Type of termination		screw M3	screw M3
Contact screw torque		max. 0,5 N/m	max. 0,5 N/m
Suitable cables		5 mm to 7 mm diameter	6 mm to 9 mm diameter
Mounting		central screw M3x32,5	central screw M3x32,5
Material			
Contact holder material		PA6 GF	PA6 GF
Housing material		PA12	PA12
Environmental conditions			
Protection class (EN 60529)		IP 65 when correctly assembled	IP 65 when correctly assembled
Pollution severity (EN 60664-1)		3	3
Temperature range		-20°C to + 80°C	-20°C to + 80°C
Inflammability class			
Contact holder		HB - UL 94	HB - UL 94
Housing		HB - UL 94	HB - UL 94
Packaging			
Packaging unit / Weight approx.		100 pieces / 2,5Kg	100 pieces / 2,5Kg
Box dimensions		29 x 15 x 18 cm	29 x 15 x 18 cm
Other accessories options			
to be ordered separately see pages 171-175		NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag

Valve Connectors KA1 series

SELF - ASSEMBLY CABLE



EN175301-803	EN175301-803	EN175301-803	EN175301-803
A	A	A	A
P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit
transparent	transparent	transparent	transparent
2+PE	2+PE	2+PE	2+PE
KA132T54T9	KA132T54T1	KA132C54T9	KA132C54T1
order no. KA132T57T9	order no. KA132T57T1		
order no. KA132T5AT9	order no. KA132T5AT1		
PG9 (M16x1,5 on request)	PG11	PG9 (M16x1,5 on request)	PG11
1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal
6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
24 V AC/DC	24 V AC/DC	24 V AC/DC	24 V AC/DC
4 A	4 A	4 A	4 A
TVS Vbr max.=37,8V Peak=400W	TVS Vbr max.=37,8V Peak=400W	Filter RC C=0,1 µF R=100 Ω	Filter RC C=0,1 µF R=100 Ω
yellow	yellow	yellow	yellow
15mΩ max.	15mΩ max.	15mΩ max.	15mΩ max.
III	III	III	III
screw M3	screw M3	screw M3	screw M3
max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m
5 mm to 7 mm diameter	6 mm to 9 mm diameter	5 mm to 7 mm diameter	6 mm to 9 mm diameter
central screw M3x32,5	central screw M3x32,5	central screw M3x32,5	central screw M3x32,5
PA6 GF	PA6 GF	PA6 GF	PA6 GF
PA12	PA12	PA12	PA12
IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled
3	3	3	3
-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg
29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm
NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag
Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag
Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag

Form A - EN 175301-803 (DIN43650) / ISO 4400



Form A - EN 175301-803 (DIN43650) / ISO 4400

Product description		EN175301-803	EN175301-803
Standard		EN175301-803	EN175301-803
Construction type		A	A
Description		P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and VDR protective circuit (varistor)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and VDR protective circuit (varistor)
Housing colour		transparent	transparent
Number of contacts		2+PE	2+PE
Order no.		KA132V54T9	KA132V55T9
Other options on request	led colour red led colour green	order no. KA132V57T9 order no. KA132V5AT9	order no. KA132V58T9 order no. KA132V5BT9
Cable gland		PG9 (M16x1,5 on request)	PG9 (M16x1,5 on request)
Max. conductor size		max. 1,5mm ² without splice/terminal	max. 1,5mm ² without splice/terminal
Drawing			
Technical data			
Pin dimension		6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
Voltage		24 V AC/DC	115 V AC/DC
Rated current max.		5 A	5 A
Suppressor		VDR 30 Vrms 0,9 Joule	VDR 130 Vrms 4,5 Joule
LED colour		yellow	yellow
Contact resistance		15mΩ max.	15mΩ max.
Overvoltage category		III	III
Type of termination		screw M3	screw M3
Contact screw torque		max. 0,5 N/m	max. 0,5 N/m
Suitable cables		5 mm to 7 mm diameter	5 mm to 7 mm diameter
Mounting		central screw M3x32,5	central screw M3x32,5
Material			
Contact holder material		PA6 GF	PA6 GF
Housing material		PA12	PA12
Environmental conditions			
Protection class (EN 60529)		IP 65 when correctly assembled	IP 65 when correctly assembled
Pollution severity (EN 60664-1)		3	3
Temperature range		-20°C to + 80°C	-20°C to + 80°C
Inflammability class			
Contact holder		HB - UL 94	HB - UL 94
Housing		HB - UL 94	HB - UL 94
Packaging			
Packaging unit / Weight approx.		100 pieces / 2,5Kg	100 pieces / 2,5Kg
Box dimensions		29 x 15 x 18 cm	29 x 15 x 18 cm
Other accessories options			
to be ordered separately see pages 171-175		NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag

Valve Connectors KA1 series

SELF - ASSEMBLY CABLE



EN175301-803	EN175301-803	EN175301-803	EN175301-803
A	A	A	A
P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and VDR protective circuit (varistor) transparent	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and VDR protective circuit (varistor) transparent	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and VDR protective circuit (varistor) transparent	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and VDR protective circuit (varistor) transparent
2+PE KA132V56T9	2+PE KA132V54T1	2+PE KA132V55T1	2+PE KA132V56T1
order no. KA132V59T9	order no. KA132V57T1	order no. KA132V58T1	order no. KA132V59T1
order no. KA132V5CT9	order no. KA132V5AT1	order no. KA132V5BT1	order no. KA132V5CT1
PG9 (M16x1,5 on request)	PG11	PG11	PG11
max. 1,5mm ² without splice/terminal	max. 1,5mm ² without splice/terminal	max. 1,5mm ² without splice/terminal	max. 1,5mm ² without splice/terminal
6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
230 V AC/DC	24 V AC/DC	115 V AC/DC	230 V AC/DC
5 A	5 A	5 A	5 A
VDR 275 Vrms 8,6 Joule	VDR 30 Vrms 0,9 Joule	VDR 130 Vrms 4,5 Joule	VDR 275 Vrms 8,6 Joule
yellow	yellow	yellow	yellow
15mΩ max.	15mΩ max.	15mΩ max.	15mΩ max.
III	III	III	III
screw M3	screw M3	screw M3	screw M3
max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m
5 mm to 7 mm diameter	6 mm to 9 mm diameter	6 mm to 9 mm diameter	6 mm to 9 mm diameter
central screw M3x32,5	central screw M3x32,5	central screw M3x32,5	central screw M3x32,5
PA6 GF	PA6 GF	PA6 GF	PA6 GF
PA12	PA12	PA12	PA12
IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled
3	3	3	3
-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg
29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm
NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag
Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag
Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag

Form A - EN 175301-803 (DIN43650) / ISO 4400