



<b>Product description</b>			
Standard	Industrial standard (9,4 mm)	Industrial standard (9,4 mm)	
Construction type	C	C	
Description	P9,4 connector with screw terminals NBR flat gasket (PE) earth position H6	P9,4 connector with screw terminals NBR flat gasket (PE) earth position H6	
Housing colour	black	black	
Number of contacts	2+PE	3+PE	
Order no.	<b>KD136000B7</b>	<b>KD046000B7</b>	
Other options on request	order no. <b>KD135000B7</b> earth pos. H12	order no. <b>KD045000B7</b> earth pos. H12	
Cable gland	PG7	PG7	
Max. conductor size	1,0mm <sup>2</sup> without splice/terminal	1,0mm <sup>2</sup> without splice/terminal	
Drawing		 	 
<b>Technical data</b>			
Pin dimension	3,6 x 0,5mm; 2,8 x 0,5mm	3,6 x 0,5mm; 2,8 x 0,5mm	
Voltage	250 V AC/DC max.	250 V AC/DC max.	
Rated current max.	6 A ( IEC512-3 test 5b )	6 A ( IEC512-3 test 5b )	
Suppressor			
LED colour			
Contact resistance	15mΩ max.	15mΩ max.	
Overvoltage category	III	III	
Type of termination	headless screw M3	headless screw M3	
Contact screw torque	max. 0,2 N/m	max. 0,2 N/m	
Suitable cables	4 mm to 6 mm diameter	4 mm to 6 mm diameter	
Mounting	central screw M3x27,5	central screw M3x27,5	
<b>Material</b>			
Contact holder material	PA6 GF	PA6 GF	
Housing material	PA6 GF	PA6 GF	
<b>Environmental conditions</b>			
Protection class (EN 60529)	IP 65 when correctly assembled	IP 65 when correctly assembled	
Pollution severity (EN 60664-1)	3	3	
Temperature range	-40 °C to + 100 °C	-40 °C to + 100 °C	
<b>Inflammability class</b>			
Contact holder	HB - UL 94	HB - UL 94	
Housing	HB - UL 94	HB - UL 94	
<b>Packaging</b>			
Packaging unit / Weight approx.	1000 pieces / Kg 13	1000 pieces / Kg 13	
Box dimensions	80 x 30 x 22 cm	80 x 30 x 22 cm	
<b>Other accessory options</b>			
to be ordered separately see pages 171-175	NBR profile gasket 100 pcs in bag	NBR profile gasket 100 pcs in bag	